

# CYCLONIK SERIES

Residential

## Specific characteristics of this series:

- ✓ Vacuum both dry and liquid substances\*.
- ✓ Always maintains the same superior suction power.
- ✓ Vacuum with cyclonic effect.
- ✓ No filter or bag needed.
- ✓ Lifetime warranty casing.

### Outdoor exhaust required

This series works with a cyclonic filtration system. An outdoor exhaust will let the microdusts, allergens and odors to be evacuated outside.

### Versatile!

Standard version without bag or filter.

Available options :

- Foam filter
- Filter cartridge
- Float
- HEPA filter

### Float

If the device is used to vacuum liquid substances, we recommend the use of a float that will indicate the maximum capacity by cutting off the vacuum.

### Capacity of 10 imp. gal. / 46 L\*\*

The largest tank available in the residential line.

**WET DRY**

### Coal dust collector

### No filter or bag needed

Simply empty and clean the bucket when required.

### Maximum liquid level

A sticker indicating the maximum liquid level recommended. Beyond this line, the bucket gets very heavy when it comes time to empty it.



\* Except model DF1R630 with foam filter for which we recommend not suck up liquids unless used with the liquid interceptor (RECU-02DVI).

\*\* The DF1R630 model has a capacity of 9 imp. gal. / 41 L.



# Power and Quality You Can Trust



- Vacuum both dry and liquid substances
- No filter bag to replace
- Always maintains the same superior suction power.
- Vacuum with cyclonic effect.
- Lifetime warranty on the casing.
- Powerful Domel Tangential By-Pass motors, Europe's most superior central vacuum motor.



Fitted With 1 x Powerful Tangential By-Pass Motor

## Standard Cleaning Kit



## Optional Tools



# Cyclonic Series

## DF1R700

DF1R700: Float option

- Cyclonic central vacuum without bag and filter
- Wet and dry vacuuming
- Outdoor exhaust required
- 6' (1.8 m) electrical cord
- Lifetime warranty casing



TECHNICAL DATA VALUES

### UNIT

AIRWATTS	700
mmH <sub>2</sub> O	3500
m <sup>3</sup> /h	246
DECIBEL	62 dB at 10' / 62 dB at 3 m
VOLTAGE	230 - 240
WATTS	1650
HEIGHT	49" / 122.5 cm
DIAMETER	15" / 38 cm
CAPACITY	6 imp. gal. / 29 L
WEIGHT	49 lb / 22 kg
FUSE	12 A
DRAIN	2" / 50 mm

### MOTOR

MOTOR CODE	MOTE-53
QUANTITY	1
DIAMETER	6.6" / 17 cm
STAGES	2 tangential discharge
FANS	9
AMPS	7.5
CARBON BRUSHES	1500+ life hours (Curved brush)
High efficient cooling system	
Locked-rotor, blocked cooling air and running overload protection	
New patent-pending bearing protection for wet applications	
Noise: improved sound quality	
Soft start starting at 40%	

CSA Certified Product